

SAFETY DATA SHEET
708 SELF LEVEL FLOOR COMPOUND

Page 1
Issued: 16/05/2003
Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: 708 SELF LEVEL FLOOR COMPOUND

Product code: SEL - ALL SIZES

Use / description of product: Irritant.

Company name: EVERBUILD BUILDING PRODUCTS LTD

SITE 41 KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

LEEDS

WEST YORKSHIRE

LS9 0SW

ENGLAND

Tel: (0044) 113 240 3456

Fax: (0044) 113 200 9418

2. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients: ORDINARY PORTLAND CEMENT 30-50%

CAS: 65997-15-1

[Xi] R41; [-]; [-]

- HIGH ALUMINA CEMENT 1-10%

CAS: 65997-16-2

[Xi] R41; [-]; [-]

- HYDRATED LIME 1-10%

CAS: 1305-62-0

[Xi] R38; [Xi] R41

3. HAZARDS IDENTIFICATION

Main hazards: Risk of serious damage to eyes. Contact with wet cement, wet concrete or wet mortar may cause irritation, dermatitis or burns. Contact between cement powder and body fluids (eg sweat and eye fluid) may also cause skin and respiratory irritation, dermatitis or burns.

Other hazards: Contains Chromium VI. May produce an allergic reaction

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: Exposure may cause coughing or wheezing.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

[cont...]

SAFETY DATA SHEET
708 SELF LEVEL FLOOR COMPOUND

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Do not create dust.

Environmental precautions: Do not discharge into drains or rivers.

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Avoid the formation or spread of dust in the air.

Storage conditions: Keep container tightly closed. Store in original containers between +5 and +25°C. Storage outside these parameters will dramatically reduce shelf life and invalidates all product warranties.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ingredients: ORDINARY PORTLAND CEMENT
TWA (8 hr exposure limit): 10mg/m³ (OES)

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protective device with particle filter. Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Powder

Colour: Grey

Odour: Odourless

Evaporation rate: Negligible

Solubility in water: Slightly soluble

Relative density: 1.8

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Moist air. Humidity.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Chronic toxicity: May cause sensitisation by skin contact.

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Persistence and degradability: No data available.

Bioaccumulative potential: No data available.

Other adverse effects: No data available.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Dispose of according to local or national legislation

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: -

Shipping name: "NOT SUBJECT TO ADR"

IMDG / IMO

UN no: -

IATA / ICAO

UN no: -

15. REGULATORY INFORMATION

Hazard symbols: Irritant.



Risk phrases: R41: Risk of serious damage to eyes.

Contact with wet cement, wet concrete or wet mortar may cause irritation, dermatitis or burns.

Contact between cement powder and body fluids (eg sweat and eye fluid) may also cause skin and respiratory irritation, dermatitis or burns.

SAFETY DATA SHEET
708 SELF LEVEL FLOOR COMPOUND

Safety phrases: S2: Keep out of the reach of children.
S22: Do not breathe dust.
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S28: After contact with skin, wash immediately with plenty of water.
S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.
S46: If swallowed, seek medical advice immediately and show this container or label.

Precautionary phrases: Contains chromium (VI). May produce an allergic reaction.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. ADDITIONAL INFORMATION

Risk phrases used in s.2: R41: Risk of serious damage to eyes.
Contact with wet cement, wet concrete or wet mortar may cause irritation, dermatitis or burns.
Contact between cement powder and body fluids (eg sweat and eye fluid) may also cause skin and respiratory irritation, dermatitis or burns.
R38: Irritating to skin.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.