

SAFETY DATA SHEET

PDQ330 GAP FILLING FLOOR GRIPPER ADHESIVE

Page 1

Issued: 19/07/2005

Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: PDQ330 GAP FILLING FLOOR GRIPPER ADHESIVE

Product code: PDQ330

Use / description of product: Highly flammable.

Company name: EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

LEEDS

WEST YORKSHIRE

LS9OSW

ENGLAND

Tel: 0044 113 240 3456

Fax: 0044 113 240 0024

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: ETHYL METHYL KETONE 1-10%

EINECS: 201-159-0 CAS: 78-93-3

[F] R11; [Xi] R36; [Xi] R66; [-] R67

- TOLUENE 1-10%

EINECS: 203-625-9 CAS: 108-88-3

[F] R11; [Xi] R38; [Xn] R48/20; [Xn] R63; [Xn] R65; [-] R67

- NAPHTHA (PETROLEUM) HYDROTREATED LIGHT 1-10%

[F] R11; [Xi] R38; [N] R51/53; [Xn] R65; [-] R67

3. HAZARDS IDENTIFICATION

Main hazards: Highly flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

[cont...]

SAFETY DATA SHEET
PDQ330 GAP FILLING FLOOR GRIPPER ADHESIVE

Ingestion: Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

Exposure hazards: Highly flammable. In combustion emits toxic fumes. May form flammable / explosive dust-air mixture.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. Notify the police and fire brigade immediately. Eliminate all sources of ignition.

Environmental precautions: Do not discharge into drains or rivers.

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

7. HANDLING AND STORAGE

Handling requirements: Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition. Store in original containers between +5 and +25°C. Storage outside these parameters will dramatically reduce shelf life and invalidates all product warranties.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: ETHYL METHYL KETONE

WEL (8 hr exposure limit): 600 mg/m³ WEL (15 min exposure limit): 899 mg/m³

- TOLUENE

WEL (8 hr exposure limit): 191 mg/m³ WEL (15 min exposure limit): 574 mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour concentration is above OES or if ventilation is poor

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES**State:** Paste**Colour:** Beige**Odour:** Pungent**Evaporation rate:** Fast**Oxidising:** Non-oxidising (by EC criteria)**Solubility in water:** Insoluble**Also soluble in:** Most organic solvents.**Viscosity:** Viscous**Boiling point/range°C:** 64**Flash point°C:** 0-21**Relative density:** 1.34**VOC g/l:** 30%**10. STABILITY AND REACTIVITY****Stability:** Stable under normal conditions. Stable at room temperature.**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.**Materials to avoid:** Strong oxidising agents. Strong acids.**Haz. decomp. products:** In combustion emits toxic fumes.**11. TOXICOLOGICAL INFORMATION****Hazardous ingredients:** TOLUENE

IVN RAT LD50 1960 mg/kg

ORL MUS LD50 2 gm/kg

ORL RAT LD50 6900 mg/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.**12. ECOLOGICAL INFORMATION****Persistence and degradability:** No data available.**Bioaccumulative potential:** No data available.**Other adverse effects:** Harmful to aquatic organisms.**13. DISPOSAL CONSIDERATIONS****Disposal operations:** Dispose of according to local or national legislation**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.**14. TRANSPORT INFORMATION**

ADR / RID

UN no: 1133 ADR Class: 3
Packing group: II Classification code: F1
Shipping name: ADHESIVES
Labelling: 3 Hazard ID no: 33



IMDG / IMO

UN no: 1133 Class: 3
Packing group: II EmS: F-E,S-D
Marine pollutant: . Labelling: 3

IATA / ICAO

UN no: 1133 Class: 3
Packing group: II Packing instructions: 305(P&CA); 307(CAO)
Labelling: 3

15. REGULATORY INFORMATION

Hazard symbols: Highly flammable.



Risk phrases: R11: Highly flammable.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: S2: Keep out of the reach of children.

S7/9: Keep container tightly closed and in a well-ventilated place.

S23: Do not breathe vapour.

S16: Keep away from sources of ignition - No smoking.

S46: If swallowed, seek medical advice immediately and show this container or label.

S51: Use only in well-ventilated areas.

S33: Take precautionary measures against static discharges.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.2: R11: Highly flammable.
R36: Irritating to eyes.
R66: Repeated exposure may cause skin dryness or cracking.
R67: Vapours may cause drowsiness and dizziness.
R38: Irritating to skin.
R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R63: Possible risk of harm to the unborn child.
R65: Harmful: may cause lung damage if swallowed.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.