

SAFETY DATA SHEET
PDQ 550 PU WOOD FLOOR ADHESIVE

Page 1
Issued: 19/07/2005
Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: PDQ 550 PU WOOD FLOOR ADHESIVE

Product code: PDQ550CART/FOIL

Use / description of product: Harmful. Product is not classified as flammable (R10) because its speed of combustion is lower than the limit of the regulation

Company name: EVERBUILD BUILDING PRODUCTS LTD
SITE 41, KNOWSTHORPE WAY
CROSS GREEN INDUSTRIAL ESTATE
LEEDS
WEST YORKSHIRE
LS9OSW
ENGLAND
Tel: 0044 113 240 3456
Fax: 0044 113 240 0024

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: DIPHENYLMETHANE-4,4'-DI-ISOCYANATE <1%
EINECS: 202-966-0 CAS: 101-68-8
[Xn] R20; [Xi] R36/37/38; [Sens.] R42/43

3. HAZARDS IDENTIFICATION

Main hazards: May cause sensitisation by inhalation and skin contact.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat. There may be shortness of breath due to congestion of the lungs.

Inhalation: Drowsiness or mental confusion may occur. Headache, dizziness, nausea

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If conscious, ensure the casualty sits or lies down. If unconscious and breathing is OK, place in the recovery position. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

[cont...]

5. FIRE-FIGHTING MEASURES

Extinguishing media: Carbon dioxide. Alcohol resistant foam. Dry chemical powder.

Exposure hazards: In combustion emits toxic fumes of carbon monoxide. In combustion emits toxic fumes of hydrogen cyanide. In combustion emits toxic fumes of nitrogen oxides.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Do not attempt to take action without suitable protective clothing - see section 8 of SDS.
Eliminate all sources of ignition. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

Environmental precautions: Do not discharge into drains or rivers.

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance.
Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Smoking is forbidden. Ensure there is sufficient ventilation of the area. Do not handle in a confined space.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Store in original containers between +5 and +25°C. Storage outside these parameters will dramatically reduce shelf life and invalidates all product warranties.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: DIPHENYLMETHANE-4,4'-DI-ISOCYANATE
WEL (8 hr exposure limit): 0.02 mg/m³ WEL (15 min exposure limit): 0.07 mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour concentration is above OES or if ventilation is poor

Hand protection: Gloves (solvent-resistant).

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Paste

Colour: Beige

Odour: Barely perceptible odour

Evaporation rate: Slow

Solubility in water: Insoluble

Also soluble in: Most organic solvents.**Viscosity:** Highly viscous**Boiling point/range°C:** 137**Flash point°C:** >100**Autoflammability°C:** >200**Relative density:** 1.17**10. STABILITY AND REACTIVITY****Stability:** Stable under normal conditions.**Conditions to avoid:** Heat. Moist air.**Materials to avoid:** Strong oxidising agents. Strong acids. Alcohols. Amines.**Haz. decomp. products:** In combustion emits toxic fumes.**11. TOXICOLOGICAL INFORMATION****Hazardous ingredients:** DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

ORL MUS LD50 2200 mg/kg

ORL RAT LD50 9200 mg/kg

Chronic toxicity: May cause sensitisation by inhalation.**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.**12. ECOLOGICAL INFORMATION****Persistence and degradability:** No data available.**Bioaccumulative potential:** No data available.**Other adverse effects:** No data available.**13. DISPOSAL CONSIDERATIONS****Disposal operations:** Dispose of according to local or national legislation**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.**14. TRANSPORT INFORMATION****ADR / RID****UN no:** -**Shipping name:** "NOT SUBJECT TO ADR"**IMDG / IMO****UN no:** -**IATA / ICAO****UN no:** -

SAFETY DATA SHEET
PDQ 550 PU WOOD FLOOR ADHESIVE

15. REGULATORY INFORMATION

Hazard symbols: Harmful.



Risk phrases: R42/43: May cause sensitisation by inhalation and skin contact.

Safety phrases: S2: Keep out of the reach of children.

S24: Avoid contact with skin.

S23: Do not breathe vapour.

S37: Wear suitable gloves.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S63: In case of accident by inhalation, remove casualty to fresh air and keep at rest.

Precautionary phrases: Contains isocyanates. See information supplied by the manufacturer.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.2: R20: Harmful by inhalation.

R36/37/38: Irritating to eyes, respiratory system and skin.

R42/43: May cause sensitisation by inhalation and skin contact.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.