

# SAFETY DATA SHEET

POLYURETHANE 40 ADHESIVE AND SEALANT - ALL COLOURS

Page 1

Issued: 08/04/2003

Revision No: 1

## 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

**Product name:** POLYURETHANE 40 ADHESIVE AND SEALANT - ALL COLOURS

**Product code:** PU40 - all colours

**Use / description of product:** Harmful. Product is not classified as flammable (R10) because its speed of combustion is lower than the limit of the regulation

**Company name:** EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

LEEDS

WEST YORKSHIRE

LS9 OSW

ENGLAND

Tel: +44 (0) 113 240 3456

Fax: +44 (0) 113 200 9418

## 2. COMPOSITION / INFORMATION ON INGREDIENTS

**Hazardous ingredients:** XYLENE 1-10%

EINECS: 215-535-7 CAS: 1330-20-7

[-] R10; [Xn] R20/21; [Xi] R38

- DIPHENYLMETHANE-4,4'-DI-ISOCYANATE <1%

EINECS: 202-966-0 CAS: 101-68-8

[Xn] R20; [Xi] R36/37/38; [Sens.] R42/43

- DISTILLATES, PETROLEUM, HYDROTREATED, LIGHT 1-10%

CAS: 64742-47-8

[Xn] R65

## 3. HAZARDS IDENTIFICATION

**Main hazards:** May cause sensitisation by inhalation and skin contact.

## 4. FIRST AID MEASURES (SYMPTOMS)

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat. There may be shortness of breath due to congestion of the lungs.

**Inhalation:** Drowsiness or mental confusion may occur. Headache, dizziness, nausea

## 4. FIRST AID MEASURES (ACTION)

**Skin contact:** Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. If conscious, ensure

[cont...]

the casualty sits or lies down. If unconscious and breathing is OK, place in the recovery position. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

## 5. FIRE-FIGHTING MEASURES

**Extinguishing media:** Carbon dioxide. Alcohol resistant foam. Dry chemical powder.

**Exposure hazards:** In combustion emits toxic fumes of carbon monoxide. In combustion emits toxic fumes of hydrogen cyanide. In combustion emits toxic fumes of nitrogen oxides.

**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Eliminate all sources of ignition. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

**Environmental precautions:** Do not discharge into drains or rivers.

**Clean-up procedures:** Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

## 7. HANDLING AND STORAGE

**Handling requirements:** Smoking is forbidden. Ensure there is sufficient ventilation of the area. Do not handle in a confined space.

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. Store in original containers between +5 and +25°C. Storage outside these parameters will dramatically reduce shelf life and invalidates all product warranties.

**Suitable packaging:** Must only be kept in original packaging.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Hazardous ingredients:** XYLENE

TWA (8 hr exposure limit): 220 mg/m<sup>3</sup> STEL (15 min exposure limit): 441 mg/m<sup>3</sup> (OES)

- DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

TWA (8 hr exposure limit): 0.02 mg/m<sup>3</sup> STEL (15 min exposure limit): 0.07 mg/m<sup>3</sup> (OES)

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour concentration is above OES or if ventilation is poor

**Hand protection:** Gloves (solvent-resistant).

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**State:** Paste

**Colour:** Various

**Odour:** Aromatic

**Evaporation rate:** Slow

**Solubility in water:** Insoluble

**Also soluble in:** Most organic solvents.

**Viscosity:** Highly viscous

**Boiling point/range°C:** 137

**Flammability limits %: lower:** 0.6

**upper:** 8

**Flash point°C:** 40-55

**Autoflammability°C:** >200

**Relative density:** 1.17

## 10. STABILITY AND REACTIVITY

**Stability:** Stable under normal conditions.

**Conditions to avoid:** Heat. Moist air.

**Materials to avoid:** Strong oxidising agents. Strong acids. Alcohols. Amines.

**Haz. decomp. products:** In combustion emits toxic fumes.

## 11. TOXICOLOGICAL INFORMATION

**Hazardous ingredients:** XYLENE

ORL MUS LD50 2119 mg/kg

ORL RAT LD50 4300 mg/kg

SCU RAT LD50 1700 mg/kg

- DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

ORL MUS LD50 2200 mg/kg

ORL RAT LD50 9200 mg/kg

**Chronic toxicity:** May cause sensitisation by inhalation.

**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

## 12. ECOLOGICAL INFORMATION

**Persistence and degradability:** No data available.

**Bioaccumulative potential:** No data available.

**Other adverse effects:** No data available.

## 13. DISPOSAL CONSIDERATIONS

**Disposal operations:** Dispose of according to local or national legislation

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## 14. TRANSPORT INFORMATION

**ADR / RID****UN no:** -**Shipping name:** "NOT SUBJECT TO ADR"**IMDG / IMO****UN no:** -**IATA / ICAO****UN no:** -**15. REGULATORY INFORMATION****Hazard symbols:** Harmful.**Risk phrases:** R42/43: May cause sensitisation by inhalation and skin contact.**Safety phrases:** S2: Keep out of the reach of children.

S23: Do not breathe vapour.

S24: Avoid contact with skin.

S37: Wear suitable gloves.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S63: In case of accident by inhalation, remove casualty to fresh air and keep at rest.

**Precautionary phrases:** Contains isocyanates. See information supplied by the manufacturer.**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.**16. OTHER INFORMATION****Risk phrases used in s.2:** R10: Flammable.

R20/21: Harmful by inhalation and in contact with skin.

R38: Irritating to skin.

R20: Harmful by inhalation.

R36/37/38: Irritating to eyes, respiratory system and skin.

R42/43: May cause sensitisation by inhalation and skin contact.

R65: Harmful: may cause lung damage if swallowed.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.