

# SAFETY DATA SHEET

STICK 2 ALL PURPOSE CLEAR ADHESIVE

Page 1

Issued: 29/11/2003

Revision No: 1

## 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

**Product name:** STICK 2 ALL PURPOSE CLEAR ADHESIVE

**Company name:** Everbuild Building Products Ltd

Site 41, Knowsthorpe Way

Cross Green Industrial Estate

Leeds

West Yorkshire

LS9 OSW

England

Tel: 0044 113 240 3456

Fax: 0044 113 240 0024

## 2. COMPOSITION / INFORMATION ON INGREDIENTS

**Hazardous ingredients:** ACETONE 30-50%

EINECS: 200-662-2 CAS: 67-64-1

[F] R11; [Xi] R36; [Xi] R66; [-] R67

- ETHANOL 10-30%

EINECS: 200-578-6 CAS: 64-17-5

[F] R11

## 3. HAZARDS IDENTIFICATION

**Main hazards:** Highly flammable. Irritating to eyes. Repeated exposure may cause skin dryness or cracking.

Vapours may cause drowsiness and dizziness.

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

## 4. FIRST AID MEASURES (SYMPTOMS)

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

## 4. FIRST AID MEASURES (ACTION)

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

## 5. FIRE-FIGHTING MEASURES

**Extinguishing media:** Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

[cont...]

## SAFETY DATA SHEET

### STICK 2 ALL PURPOSE CLEAR ADHESIVE

**Exposure hazards:** Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

#### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

#### 7. HANDLING AND STORAGE

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

**Storage conditions:** Store in original containers between +5 and +25°C. Storage outside these parameters will dramatically reduce shelf life and invalidates all product warranties. Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

**Suitable packaging:** Must only be kept in original packaging.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Hazardous ingredients:** ACETONE  
TWA (8 hr exposure limit): 1210 mg/m<sup>3</sup> STEL (15 min exposure limit): 3620 mg/m<sup>3</sup> (OES)

- ETHANOL  
TWA (8 hr exposure limit): 1920 mg/m<sup>3</sup> (OES)

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency. Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour concentration is above OES or if ventilation is poor

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**9. PHYSICAL AND CHEMICAL PROPERTIES****State:** Liquid**Colour:** Colourless**Odour:** Irritating odour which may affect the eyes and respiratory system**Evaporation rate:** Fast**Solubility in water:** Slightly soluble**Also soluble in:** Ethanol. Most organic solvents.**Viscosity:** Viscous**Boiling point/range°C:** 70**Flammability limits %: lower:** 6**upper:** 36**Flash point°C:** -5**Vapour pressure:** 97mmHg@20°C**Relative density:** 0.75-0.8**pH:** n/a**VOC g/l:** 50-55%**10. STABILITY AND REACTIVITY****Stability:** Stable under normal conditions. Stable at room temperature.**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.**Materials to avoid:** Strong oxidising agents. Strong acids.**Haz. decomp. products:** In combustion emits toxic fumes.**11. TOXICOLOGICAL INFORMATION****Hazardous ingredients:** ACETONE

IVN RAT LD50 5500 mg/kg

ORL MUS LD50 3 gm/kg

ORL RAT LD50 5800 mg/kg

## • ETHANOL

IVN RAT LD50 1440 mg/kg

ORL MUS LD50 3450 mg/kg

ORL RAT LD50 7060 mg/kg

**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.**12. ECOLOGICAL INFORMATION****Mobility:** Readily absorbed into soil.**Persistence and degradability:** Only slightly biodegradable.**Bioaccumulative potential:** No data available.**Other adverse effects:** No data available.

**13. DISPOSAL CONSIDERATIONS**

**Disposal operations:** Dispose of according to local or national legislation

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**14. TRANSPORT INFORMATION****ADR / RID**

**UN no:** 1133

**ADR Class:** 3

**Packing group:** II

**Classification code:** F1

**Shipping name:** ADHESIVES

**Labelling:** 3

**Hazard ID no:** 33

**IMDG / IMO**

**UN no:** 1133

**Class:** 3

**Packing group:** II

**EmS:** F-E,S-D

**Marine pollutant:** .

**Labelling:** 3

**IATA / ICAO**

**UN no:** 1133

**Class:** 3

**Packing group:** II

**Packing instructions:** 305(P&CA); 307(CAO)

**Labelling:** 3

**15. REGULATORY INFORMATION**

**Hazard symbols:** Highly flammable.

Irritant.



**Risk phrases:** R11: Highly flammable.

R36: Irritating to eyes.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

**Safety phrases:** S2: Keep out of the reach of children.

S7/9: Keep container tightly closed and in a well-ventilated place.

S16: Keep away from sources of ignition - No smoking.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

**SAFETY DATA SHEET**  
STICK 2 ALL PURPOSE CLEAR ADHESIVE

S46: If swallowed, seek medical advice immediately and show this container or label.

S51: Use only in well-ventilated areas.

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

**16. OTHER INFORMATION**

**Risk phrases used in s.2:** R11: Highly flammable.

R36: Irritating to eyes.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.