

SAFETY DATA SHEET
LUMBERJACK WET ROT WOOD HARDENER

Page 1
Issued: 11/04/2003
Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: LUMBERJACK WET ROT WOOD HARDENER

Use / description of product: Highly flammable or extremely flammable. Irritant.

Company name: EVERBUILD BUILDING PRODUCTS LTD
SITE 41, KNOWSTHORPE WAY
CROSS GREEN INDUSTRIAL ESTATE
LEEDS
WEST YORKSHIRE
LS9 0SW
ENGLAND
Tel: +44 (0) 113 240 3456
Fax: +44 (0) 113 200 9418

2. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients: ACETONE 70-90%
CAS: 67-64-1
EINECS: 200-662-2
[F] R11; [Xi] R36; [Xi] R66; [-] R67

3. HAZARDS IDENTIFICATION

Main hazards: Highly flammable. Irritating to eyes. Repeated exposure may cause skin dryness or cracking.
Vapours may cause drowsiness and dizziness.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

[cont...]

SAFETY DATA SHEET

LUMBERJACK WET ROT WOOD HARDENER

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition. Store in original containers between +5 and +25°C. Storage outside these parameters will dramatically reduce shelf life and invalidates all product warranties.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational exposure limits

TWA (8 hr exposure limit): 1210 mg/m³ (OES)

STEL (15 min exposure limit): 3620 mg/m³ (OES)

Ingredients: ACETONE

TWA (8 hr exposure limit): 1210 mg/m³ STEL (15 min exposure limit): 3620 mg/m³ (OES)

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour concentration is above OES or if ventilation is poor

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State:	Liquid
Colour:	Colourless
Odour:	Aromatic
Evaporation rate:	Fast
Oxidising:	Non-oxidising (by EC criteria)
Solubility in water:	Miscible in all proportions
Also soluble in:	Most organic solvents.
Viscosity:	Non-viscous
Boiling point/range°C:	56
Melting point/range°C:	-95
Flammability limits %: lower:	2.5
upper:	12.8
Flash point°C:	-18
Part.coeff. n-octanol/water:	-0.24@20°C
Autoflammability°C:	465
Vapour pressure:	185mm@20°C
Relative density:	0.79

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions. Stable at room temperature.
Conditions to avoid:	Heat. Hot surfaces. Sources of ignition. Flames.
Materials to avoid:	Strong oxidising agents. Strong acids.
Haz. decomp. products:	In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Ingredients:	ACETONE
	IVN RAT LD50 5500 mg/kg
	ORL MUS LD50 3 gm/kg
	ORL RAT LD50 5800 mg/kg
Routes of exposure:	Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility:	Readily absorbed into soil.
Persistence and degradability:	Biodegradable.
Bioaccumulative potential:	No bioaccumulation potential.
Other adverse effects:	Negligible ecotoxicity.

13. DISPOSAL CONSIDERATIONS

Disposal operations:	Dispose of according to local or national legislation
NB:	The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

SAFETY DATA SHEET
LUMBERJACK WET ROT WOOD HARDENER**14. TRANSPORT INFORMATION****ADR / RID**

UN no: 1090 **ADR Class:** 3
Packing group: II **Classification code:** F1
Shipping name: ACETONE
Labelling: 3 **Hazard ID no:** 33

**IMDG / IMO**

UN no: 1090 **Class:** 3
Packing group: II **EmS:** 3-06
Marine pollutant: NO **Labelling:** 3

IATA / ICAO

UN no: 1090 **Class:** 3
Packing group: II **Packing instructions:** 305(P&CA); 307(PAO)
Labelling: 3

15. REGULATORY INFORMATION

Hazard symbols: Highly flammable.
Irritant.



Risk phrases: R11: Highly flammable.
R36: Irritating to eyes.
R66: Repeated exposure may cause skin dryness or cracking.
R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S2: Keep out of the reach of children.
S7/9: Keep container tightly closed and in a well-ventilated place.
S23: Do not breathe vapour.
S16: Keep away from sources of ignition - No smoking.
S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.
S46: If swallowed, seek medical advice immediately and show this container or label.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

SAFETY DATA SHEET
LUMBERJACK WET ROT WOOD HARDENER

16. ADDITIONAL INFORMATION

Risk phrases used in s.2: R11: Highly flammable.

R36: Irritating to eyes.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.