

SAFETY DATA SHEET

PLASBOND 65 - WHITE

Page 1

Issued: 03/02/2003

Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: PLASBOND 65 - WHITE

Product code: PLAS100

Use / description of product: Highly flammable or extremely flammable. Irritant.

Company name: EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

LEEDS

WEST YORKSHIRE

LS9 OSW

ENGLAND

Tel: +44 (0) 113 240 3456

Fax: +44 (0) 113 200 9418

2. COMPOSITION / INFORMATION ON INGREDIENTS

- Hazardous ingredients:** TETRAHYDROFURAN 30-50%
- EINECS: 203-726-8 CAS: 109-99-9
- [F] R11; [-] R19; [Xi] R36/37
- ETHYL METHYL KETONE 10-30%
- EINECS: 201-159-0 CAS: 78-93-3
- [F] R11; [Xi] R36; [Xi] R66; [-] R67

3. HAZARDS IDENTIFICATION

Main hazards: Highly flammable. Irritating to eyes and respiratory system. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

[cont...]

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers. Do not use water Jet

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition. Store in original containers between +5 and +25°C. Storage outside these parameters will dramatically reduce shelf life and invalidates all product warranties.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: TETRAHYDROFURAN
TWA (8 hr exposure limit): 150 mg/m³ STEL (15 min exposure limit): 300 mg/m³ (OES)

- ETHYL METHYL KETONE
TWA (8 hr exposure limit): 600 mg/m³ STEL (15 min exposure limit): 899 mg/m³ (OES)

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour concentration is above OES or if ventilation is poor

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: White

Odour: Aromatic

Evaporation rate: Fast

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Viscosity: Viscous

Boiling point/range°C: 65

Melting point/range°C: N/D

Flammability limits %: lower: 1.5 vol%

upper: 15 vol%

Flash point°C: -21

Part.coeff. n-octanol/water: N/D

Autoflammability°C: >200°C

Vapour pressure: <200hPa @20°C

Relative density: 0.99

pH: N/A

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions. Stable at room temperature.

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: TETRAHYDROFURAN

IPR MUS LD50 1900 mg/kg

IPR RAT LD50 2900 mg/kg

ORL RAT LD50 1650 mg/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

Persistence and degradability: No data available.

Bioaccumulative potential: No data available.

Other adverse effects: No data available.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Dispose of according to local or national legislation

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: 1133

ADR Class: 3

Packing group: III

Classification code: F1

Shipping name: ADHESIVES

Labelling: 3

Hazard ID no: 33



IMDG / IMO

UN no: 1133

Class: 3

Packing group: III

EmS: 3-05

Marine pollutant: .

Labelling: 3

IATA / ICAO

UN no: 1133

Class: 3

Packing group: III

Packing instructions: 309(P&CA); 310(PAO)

Labelling: 3

15. REGULATORY INFORMATION

Hazard symbols: Highly flammable.

Irritant.



Risk phrases: R11: Highly flammable.

R36/37: Irritating to eyes and respiratory system.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S2: Keep out of the reach of children.

S7/9: Keep container tightly closed and in a well-ventilated place.

S23: Do not breathe vapour.

S24/25: Avoid contact with skin and eyes.

SAFETY DATA SHEET

PLASBOND 65 - WHITE

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

S46: If swallowed, seek medical advice immediately and show this container or label.

Water hazard class: 2

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.2: R11: Highly flammable.

R19: May form explosive peroxides.

R36/37: Irritating to eyes and respiratory system.

R36: Irritating to eyes.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.