

EVERBUILD TROWEL MASTIC

DESCRIPTION

EVERBUILD TROWEL MASTIC is premium oil based mastic for perimeter pointing around wood and metal window and doorframes. Trowel applied. Forms a weathertight seal. Also suitable for repointing brickwork and for bedding windows or doorframes into their surrounds.

BENEFITS

- * Easier to apply than most competitive mastics.
- * Extended shelf life.
- * Added plasticiser (polybutene) improves adhesion and helps prevent cracking.

AREAS FOR USE

- * Pointing around/bedding in windows and door frames
- * Pointing brickwork.

LIMITATIONS

- Unsuitable for plastic frames heat absorbing glass.

SURFACE PREPARATION

All surfaces must be clean, dry, free from dust, grease and other contamination.

APPLICATION

Apply using a thin pointing trowel or putty knife, working well into the joint and ensuring no voids remain. Finish smooth to a triangular fillet. When used for fillet pointing between frame and surround, joints should be a minimum width of 10mm with a minimum depth of 6mm.

OVERPAINTING AND MAINTENANCE

Product may be fully protected with an undercoat and top coat after a surface skin has formed; i.e. after 7 - 28 days. This will prolong the working life, but is not essential. Make good any defects on an annual basis.

SPECIFIC DATA

APPEARANCE:	Thick buff or red paste.
S.G (20°C):	2.0 gcm ³ (approx)
MOVEMENT ACCOM.	Low (5% total)
OIL CONTENT:	10% min.
APPLICATION TEMP.	5°C to 40°C.
SERVICE TEMP:	-20 to 50°C.
SERVICE LIFE:	Up to 15 years when applied according to the manufacturers directions.
COVERAGE	For facing, usage will be approximately 15 linear metres per kg for a triangular fillet with a 10mm face section.

HEALTH AND SAFETY

Safe in normal use. Do not eat or drink during use. Remove product with soap and water. If product enters eyes, rinse immediately with cold water and seek medical attention if irritation persists. If ingested, give plenty of water to drink and seek medical attention. See separate 16 point data sheet for full assessment.

STORAGE

Store at moderate temperatures in original containers. Any surface oil will blend in after mixing by hand.

SHELF LIFE

Up to four months when stored according to manufacturers instructions.