

EVERFLEX BATH AND KITCHEN SEALANT

DESCRIPTION

EVERFLEX BATH AND KITCHEN SEALANT is an acrylic sealant, suitable for general sealing in and around the kitchen and bathroom. The product contains a powerful anti-fungicide to prevent mould growth, and can be overpainted.

BENEFITS

- Permanently flexible
- Adheres to most surfaces.
- Mould resistant.
- Overpaintable.
- Easy clean up - wipe with wet cloth.

AREAS FOR USE

- Sealing around kitchen worktops etc.
- Internal sealing around timber and metal window and door frames.
- Internal sealing around PVCu window and door frames.
- Sealing around baths, sanitary ware, basins and ceramics.

LIMITATIONS

- Protect from water for a minimum of 24 hours after application. Note that damp or humid conditions will significantly extend the cure time. Do not expose to water until fully cured. If a quicker cure is required, use GENERAL PURPOSE SILICONE (6 hour cure).
- Not for use in conjunction with bitumen or asphalt.
- Do not attempt to abrade when cured.
- Do not use around shower trays. Use GENERAL PURPOSE SILICONE for greater movement capabilities
- Do not overpaint until a surface skin has formed. Overpainting is not necessary.
- Note: this product is a flexible. Certain poor quality paints (especially certain vinyl mattes) have very little movement in the dry film. It is possible for the dry paint film to crack if movement is excessive.

SURFACE PREPARATION

All surfaces must be clean and dust free. All loose or flaking surface coatings, and old sealant and mastic joints, should be removed before application. Highly porous substrates such as new plaster

TECHNICAL DATA SHEET NO: 026

VERSION: 1/1ST MARCH 1999

PAGE: 2 of 3

PRINT DATE: 9/16/2004

should first be primed with Everbuild PVA bond diluted 1:4 with water. This product can be applied to slightly damp, but not wet surfaces.

APPLICATION

Cut the tip of the cartridge taking care not to damage the thread. Apply nozzle and cut cleanly at an angle of 45° with an opening slightly larger than the gap to be sealed. Apply using a standard sealant gun. Best results will be obtained by keeping an even pressure on the gun trigger and keeping the gun at a constant angle to the surface being sealed. Smooth down within 20 minutes of application using a wetted spatula, piece of wood or wetted finger. Care should be taken at this point not to saturate the surface as this will delay drying. Any excess sealant etc., can be removed using a sponge and warm water.

SPECIFIC DATA

Form	Ready to use thixotropic paste	
Specific Gravity	1.62 - 1.66	
Elongation at Break (%)	250-300%	
Hardness (Shore A)	Approximately 30	
Tack Free Time	15 to 60 mins, dependent on thickness, ambient temperature and humidity	
Full Cure	3 to 5 days, dependent on thickness, ambient temperature and humidity	
Solids Content	79%	
Slump Resistance	No slump at 25°C when placed in a 20mm x 10mm vertical channel	
Application Temp. Range	+4°C to +40°C	
Service Temp. Range	-15°C to +75°C	
Chemical Resistance	Dilute Acids - Fair	Dilute Alkaline - Fair
	Aliphatic Hydrocarbons - Fair	AromaticHydrocarbons - Poor
Movement Accommodation	Low to medium (+/- 12.5%)	
Durability	Up to 15 years when used as recommended	
Shelf Life	Up to 36 months when stored in unopened cartridges under cool dry conditions. AVOID FROST	
Compatibility	Can be used in contact with most building and decorating materials but should not be used against bituminous materials.	
Limitations	Should not be used in conditions of continuous immersion, below ground level, in areas of high abrasion (e.g. floor joints)	
Classification	Sealant ISO 11600 - F – 12.5P	

HEALTH AND SAFETY

TECHNICAL DATA SHEET NO: 026
PAGE: 3 of 3

VERSION: 1/1ST MARCH 1999
PRINT DATE: 9/16/2004

- Do not ingest
- Keep out of reach of children.
- Product of low hazardous nature.
- Remove from skin with soap and water.

STORAGE

Store in cool dry conditions and protect from frost.

SHELF LIFE

Use within 3 years.