

## LUMBERJACK FENCE MATE

### DESCRIPTION

LUMBER JACK FENCE MATE is an easy to use, solvent free shed and fence treatment specifically designed to provide a safe alternative to creosote without the associated hazards. The product provides a durable water repellent finish to all rough sawn timber and is totally harmless to plants and animals, both during and after application.. FENCE MATE contains carefully selected UV resistant pigments and water repellent waxes that makes the colour last up to six times longer than creosote. It is designed for use on all rough sawn garden timber including sheds, fences, gates, hutches, kennels, cold frames and trellises.

### BENEFITS

- Solvent free formulation – non-flammable, low odour, harmless to plants and animals.
- Easy to use – water clean up of spills and tools.
- Water repellent – special waxes shed water for increased durability..
- Long lasting finish.
- Available in a range of colours
- Will cover existing creosote, providing it has weathered, i.e. it is non-water repellent.

### AREAS FOR USE

- Decorating and protecting all rough sawn timber.

### LIMITATIONS

- Use only as directed. Store only in original container.
- Use only on rough sawn, never planed timber.
- Do not use if rain is imminent (within 6 hours at 20°C).
- Do not apply below 5°C (air or surface temp).
- Always keep container upright and secure at all times during storage and transit.
- Dispose of this product and packaging correctly. Do not allow to enter watercourses. It is the users responsibility to determine suitability for use. If in doubt, please contact Technical Services Department for further advice.

#### APPLICATION

**Surface Preparation.**

Surfaces must be free from grease, dust, loose material, moss, algae etc. Clean surfaces with EVERBUILD FUNGICIDAL WASH and use a wire brush for areas badly affected.

Always stir well before use. Brush uniformly onto surface ensuring an even coverage. One coat is normally sufficient, but on some very porous or bare timbers, two or three coats may be required to achieve the correct depth of colour. Allow the first coat to dry before applying the second.

Drying time will be 2-6 hours depending on temperature. Do not apply below 5°C.

**Cleaning:** Clean brushes, spillage's etc in warm soapy water.

#### SPECIFIC DATA

APPEARANCE:	Coloured solution (water based)
S.G (20°C):	1.05gcm <sup>3</sup>
M.F.F.T:	5°C
SOLIDS	5-10% w/w
DRYING TIME	2-6 hours
COVERAGE:	1 litre will cover approximately 6-12m <sup>2</sup> per coat depending on nature of surface

#### HEALTH AND SAFETY

TECHNICAL DATA SHEET NO: 805  
PAGE: 3 of 3

VERSION: 1/1<sup>ST</sup> FEB 2000  
PRINT DATE: 16/09/2004

Product is of low hazard and non flammable, however the following precautions are advised.  
Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with copious water and seek medical attention. Wash splashes from skin with soap and water before product dries. Wear gloves, goggles and overalls during application. Keep out of reach of children

<b>STORAGE</b>
----------------

Store at moderate temperatures in original containers. PROTECT FROM FROST.

<b>SHELF LIFE</b>
-------------------

12 months when stored according to manufacturers instructions,