

LUMBER JACK WET ROT WOOD HARDENER

DESCRIPTION

LUMBER JACK WET ROT WOOD HARDENER is a highly penetrative solution of selected resins in solvent which soaks deep into the fibers of decaying wood and dries to leave the wood hard and resistant to further moisture penetration. The resin-modified wood then becomes an ideal base for repair with LUMBER JACK HIGH PERFORMANCE WOOD FILLER. The solution is dry in 6 hours and is suitable for interior and exterior use providing a cost-effective alternative to replacing joinery affected by wet rot.

BENEFITS

- Binds together damaged wood to form a solid base for filling.
- Reduces subsequent water penetration.

AREAS FOR USE

- Repairing wood damaged by wet rot (in conjunction with LUMBER JACK HIGH PERFORMANCE WOOD FILLER in both interior and exterior applications.
- Strengthening and reinforcing and sealing both softwood and hardwood.

LIMITATIONS

- Avoid contact with glass, metal, plastics or painted surfaces.
- DO NOT use this product as a surface treatment.
- Remove any residual hardener from surface before filling.
- As the manufacturer cannot know all the uses its products may be put to, it is the users responsibility to determine suitability for use. If in doubt, contact technical services department for advice.

SURFACE PREPARATION

Before applying, completely remove all decayed and crumbly wood down to a solid base. Ensure the wood is clean, reasonably dry, sound and free from dust, grease etc.

APPLICATION

Shake can and decant solution into a suitable container. Apply by brush until the area is completely saturated. An enhanced hardening effect may be achieved by drilling small holes in the wood to give deeper penetration. Allow drying and removing excess hardener with a wire brush. Fill area with LUMBER JACK HIGH PERFORMANCE WOOD FILLER and sand, stain or paint as required.

Cleaning: All tools should be cleaned immediately after use with cellulose thinners

SPECIFIC DATA

BASE	Organic resin in acetone/solvent blend
CONSISTENCY	water thin clear/opaque solution
ACTIVITY	25+/- 1% w/w.
DRYING TIME	6 hours
SPECIFIC GRAVITY	ca. 0.9
FLASH POINT	-17°C

TECHNICAL DATA SHEET NO: 807
PAGE: 3 OF 4

VERSION: 1/1/10/10/99
DATE OF ISSUE:9/16/2004

HEALTH AND SAFETY

Highly Flammable
Keep away from sources of ignition – no smoking.
Keep container tightly closed and in a well ventilated place.
Avoid contact with skin and eyes.
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Keep out of reach of children

STORAGE

Store upright between 10 and 20°C in cool, dry conditions away from sources of ignition. Store as Flammable liquid.

SHELF LIFE

12 months in original containers at stated storage temperatures.