

EVERBUILD QUICK SCRIM PLASTERBOARD JOINTING TAPE

DESCRIPTION

EVERBUILD QUICK SCRIM PLASTERBOARD JOINTING TAPE is a fibreglass re-enforced plasterers tape on a roll which is backed with a pressure sensitive adhesive.

BENEFITS

- Quick and easy to apply.
- Self-adhesive – eliminates the need for pre-plastering.
- Flexible – won't bubble or blister.

AREAS FOR USE

- For jointing dry walling.
- For repairing/jointing over large cracks in plaster.
- Repairing/jointing in ceiling work.

LIMITATIONS

- Ensure surfaces are completely clean before applying tape.
- Never overlap the tape, always butt the joint.
- When applying jointing compound or plaster, ensure complete penetration through the tape to achieve optimum adhesion.

SURFACE PREPARATION

All surfaces must be clean, dry, sound and free from oil, grease and dust.

APPLICATION

Place tape into position and apply directly to joint or crack pressing down firmly to ensure good adhesion. For crack and hole repairs, the tape must be extended at least 25mm from the edge of the area to be repaired, butting (never overlapping) the tape.
Once the tape is in position, cover with jointing compound or plaster, ensuring the plaster or jointing compound penetrates the tape to achieve optimum adhesion.

SPECIFIC DATA

FINISH:

Cream matted tape

TECHNICAL DATA SHEET NO: 114
PAGE: 2 of 2

VERSION: 1/1st FEB 00
PRINT DATE: 22/9/05

ADHESIVE TYPE

Pressure sensitive

ROLL DIMENSIONS

Width: 48mm; Length 90 mtrs

HEALTH AND SAFETY.

No hazardous tape. Avoid contact with adhesive line.

STORAGE

Store in original container in cool dry conditions. Keep away from sources of ignition.

SHELF LIFE

Storage life 12 months in tightly sealed, undamaged containers.