

COLOUR MATCH WORKTOP JOINT SEALANT AND ADHESIVE

DESCRIPTION

COLOUR MATCH WORKTOP JOINT SEALANT AND ADHESIVE KIT is an acrylic based sealant designed specifically for jointing and sealing kitchen worktops. The product is supplied in an outer of nine user friendly re-sealable squeezey tubes, covering the most common kitchen laminate colours: Polar white, Oyster white, champagne, Pastel Grey, China Blue, Empire Green, Terracotta, Deep Buff and Black.

Should different shades be required, the user may simply blend together two or more of the above to achieve the desired effect.

BENEFITS

- Permanently flexible/durable polymer rich formula.
- Large colour range gives near/exact match to most common kitchen worktop colour schemes.
- Silicone and solvent free – low odour.
- Contains a fungicide to prevent mould growth.
- Adheres to all common laminates.
- Non hazardous formula – water clean up.
- Easy to apply and tool.

AREAS OF USE

- Jointing and sealing wood/laminate worktops.
- Repairing small chips and scratches in laminates.

LIMITATIONS

- Not for use in conjunction with bitumen or asphalt.
- For internal use only.
- Not for use in joints subject to load bearing stress, or severe temperatures in excess of 75°C.
- Always remove excess material before the product has fully dried.
- Do not use below 5°C.
- It is the users responsibility to determine suitability for use. If in doubt, please phone technical services department for advice.

SURFACE PREPARATION

Ensure surfaces to be sealed are sound, clean and dry.

APPLICATION

- Apply sealant to both edges and spread evenly over both surfaces.
- Bring both surfaces together and tighten connecting bolts until the joint is almost closed
- Ensure both sides of the laminate are level and fully close the connecting bolts.
- Allow the small bead of excess material forced from joint to dry for 20 minutes
- Wipe of excess with a sponge or cloth dampened with warm soapy water., working along across the joint. DO NOT OVER WET.
- Remove any excess from the area with the same sponge or cloth before the product is fully dry.

HEALTH AND SAFETY

- * Do not ingest.
- * Product of low hazardous nature.
- * Keep out of reach of children.
- * Dispose of empty packaging correctly.

STORAGE

Store in cool dry conditions and protect from frost.

SHELF LIFE

Use within 12 months.

SPECIFIC DATA

Movement accommodation:	+ or -25%
Skinning time:	30 mins @ 20°C
Cure time:	2mm per 24 hours @ 20°C
Specific gravity:	1.05
Flashpoint:	N/A
Service temperature resistance:	-15°C to + 70°C
Application temperature:	+2°C to + 30°C
Cleaning:	Uncured sealant warm water
Elongation at break:	350%
Paintability:	Excellent with most paints, varnishes or stains once fully cured,although this is not required.
Coverage:	100ml is sufficient for jointing 4 x 700mm worktop joints.